



# Premium Single Door Gastronorm Cabinets

XPI700R / XPI700L / XNI700R / XNI700L

**2** Years Parts & Labour Warranty

**2-3** Working Days Delivery

**UK** Service Support

**Manufactured** In Europe



With their impressive climate class 5 rating, the Sterling Pro Vantage premium single door upright cabinet range is perfect for intensive applications in any busy professional kitchen environment. With a robust and heavy-duty Stainless Steel design and finish, this range features an environmentally friendly R290a and R600a refrigerant, 80mm thick (CFC-free) polyurethane insulation, extra large touch screen controllers, right or left hinged doors with automatic return and forced draft evaporators with anti-corrosion covers.

Model	Type	Hinge	Gross & Nett Capacity		Temperature Range	Energy Consumption	Climate Class	Energy Rating	Dimensions (mm)		
<b>XPI700R</b>	Fridge	Right	700 ltrs	481 ltrs	-2°C to +8°C	333 kWh/year	5	A	W693	D875	H2119
<b>XNI700R</b>	Freezer	Right	700 ltrs	481 ltrs	-18°C to -22°C	2754 kWh/year	5	D	W693	D875	H2119
<b>XPI700L</b>	Fridge	Left	700 ltrs	481 ltrs	-2°C to +8°C	333 kWh/year	5	A	W693	D875	H2119
<b>XNI700L</b>	Freezer	Left	700 ltrs	481 ltrs	-18°C to -22°C	2754 kWh/year	5	D	W693	D875	H2119



# Premium Single Door Gastronorm Cabinets

**XPI700R / XPI700L / XNI700R / XNI700L**

Range Specifications				
	XPI700R Fridge	XNI700R Freezer	XPI700L Fridge	XNI700L Freezer
GTIN Code	5060750321423	5060750321393	5060750321423	5060750321393
Dimensions (mm)	W693 x D875 x H2119	W693 x D875 x H2119	W693 x D875 x H2119	W693 x D875 x H2119
Packed Dimensions	W740 x D920 x H2200	W740 x D920 x H2200	W740 x D920 x H2200	W740 x D920 x H2200
Hinge Position	Right	Right	Left	Left
Gross Capacity	700 Litres	700 Litres	700 Litres	700 Litres
Nett Capacity	481 Litres	481 Litres	481 Litres	481 Litres
Shelves Supplied	3	3	3	3
Grid Level Positions	24	24	24	24
Exterior Finish	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Interior Finish	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Temperature Range	-2°C to +8°C	-18°C to -22°C	-2°C to +8°C	-18°C to -22°C
Max Ambient	+40°C	+40°C	+40°C	+40°C
Refrigerant	R600a	R290a	R600a	R290a
Insulation Thickness	80mm	80mm	80mm	80mm
Energy Rating	A	D	A	D
Climate Class	5	5	5	5
Efficiency Index	23.80%	58.06%	23.80%	58.06%
Energy Consumption	333 kWh/year	2754 kWh/year	333 kWh/year	2754 kWh/year
Power Supply	13 amp plug	13 amp plug	13 amp plug	13 amp plug
Voltage	230/1N 50Hz	230/1N 50Hz	230/1N 50Hz	230/1N 50Hz
Wattage	157W	678W	157W	678W
Cooling System	Forced air	Forced air	Forced air	Forced air
Defrost Type	Automatic	Automatic	Automatic	Automatic
Reversible Doors	No	No	No	No
Self Closing Doors	Yes	Yes	Yes	Yes
Lighting	Yes	Yes	Yes	Yes
Lockable	Yes	Yes	Yes	Yes
Castors	Yes	Yes	Yes	Yes

Distributor:

KiD Catering Equipment, Oaktree Court Business Centre, Mill Lane, Ness, Cheshire, CH64 8TP  
Tel: 0333 123 2450

[sales@kidcateringequipment.com](mailto:sales@kidcateringequipment.com)



# Premium Single Door Gastronorm Cabinets

XPI700R / XPI700L / XNI700R / XNI700L



### High efficiency components

Low energy compressors, large area evaporators and high performing electronic fans that minimize temperature gains, reducing energy consumption.



### Integrated Stainless Steel handle

Ergonomic, Stainless Steel made, robust, perfectly integrated handle ensures practical opening of the door that avoids dust and dirt collection and is extremely easy to clean.



### Insulation - 80mm thickness

80mm thickness CFC-free, high-density (40kg/m<sup>3</sup>) polyurethane insulation, guarantees exceptional, long-term insulation and energy savings in all Vantage cabinets.



### Intelligent air circulation system

Perfect temperature consistency with its innovative airflow design that encircles the food and ensures its proper conservation.



### Rounded edge interior

Easier cleaning operations to reduce potential dirt traps and optimum hygiene.



### Removable door gasket

Removable pull-out/push-in magnetic door gasket to keep maximum hygiene and maintain the insulating properties.



### Maximum energy savings

The XPI700 refrigerator achieves the highest A Rating under the conditions defined in climate class 5, ensuring the maximum energy savings.

\*The label complies with the delegated regulation (UE) 2015/1094 of the commission of 5th May 2015



### Compact controller

Extra large, screen touch controller with energy saving strategy and HACCP alarm system, which allows an easy temperature parameter adjustment ensuring the best food preservation. It also offers a Bluetooth data logger as an option.




### Evaporation of defrost water

Hot gas coming from the compressor is used to automatically evaporate defrost water, instead of by means of heating elements, achieving even less energy consumption.



### Stamped guides, sturdy wire grids

Stamped guides with rounded edges enable more convenient cleaning operations without any difficulties. Plastic coated wire grids allow storage of different packaging types and have a maximum loading capacity of up to 40kg.



### Internal LED lighting

Low energy consumption LED lighting to display the interior, standard in all Vantage upright models.



### Self closing hinged doors

Hinged doors with automatic return for a perfect closing that minimize temperature gain and reduces energy consumption. Doors have a 120° dwell position and closes automatically at less than 90°. Door hinges are also reversible.

